

XViu Mirror with lighting # XV7038

|< 71 5/8" Inch >|



Mirror with lighting	Dimension	Weight	Order number
Sensor-Version, cEGS/IAPM0®*, LED dual light fields, 25 Watt, LED ambient light (top), 18-28 Watt starting at mirror width 52", 1 sensor switch bottom right, LED dimming function, LED (life span > 30,000 hours), LED module permanently enclosed, mirrors require a GFCI 110 V 60 Hz power source, flat plug will be supplied with mirror, LED module 3500 kelvin light color, 50 Watt			
Colors			
MB1 Champagne Matt MB2 Black Matt			
Variant			
	71 5/8" x 1 5/8" Inch		XV7038
Infobox			
Distance between sensor and reflecting surfaces = minimum 3", On/off function only possible with external wall switch, * Complies with following standards: UL 962 and CSA C22.2 No. 12-1982, Required specification for ordering:			
Additional modules de-fogging system with Auto-Off function, mirror widths 70 7/8", 71 5/8", 78 3/4", 79 1/2" 76 Watt			UV9775

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.