



Mirror cabinet	Dimension	Weight	Order number
Sensor-Version, cEGS/IAPMO®*, LED dual light fields, side in mirror glass, 2 mirror doors, 1 wooden shelf, 2 shelves (clear glass), integrated wave board for small back panel inside mirror glass, 1 sensor switch bottom LED dimming function, LED (life span > 30,000 hours), module permanently enclosed, mirror cabinets require 110 V 60 Hz power source, flat plug will be supplied wi mirror cabinet, LED module 3500 kelvin light color, 25	glass parts, right, LED a a GFCI th the		
Colors			
MB1 Champagne Matt MB2 Black Matt			
Variant			
	32 1/4" x 6 1/8" Inch		XV7132
Infobox			
* Complies with following standards: UL 962 and CSA C	22.2 No. 12-1982, Required sp	ecification for orderi	ng:
Additional modules cEGS/IAPMO®*, LED downlight for washbasin area 3500 kelvin light color, 3 Watt, LED dimming function, LED (life span > 30,000 hours), LED module permanently enclosed		UV9954	
Suitable products			
Magnetic strip in stainless steel , 3 1/2" Inch	3 1/2" Inch		UV9709
Box for mirror cabinet, 3 7/8" x 6 1/4" Inch	3 7/8" x 6 1/4" Inch		XV9948

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.