

DuraStyle Cistern # 0935100005 / 0935100085

|< 390 mm >|



| Cistern  | Dimension    | Weight          | Order number |
|--|--------------|-----------------|--------------|
| with Dual Flush mechanism, chrome, for bottom left supply, cUPC® listed*   |              |                 |              |
| <b>Colors</b>  |              |                 |              |
| 00 White Alpin   |              |                 |              |
| <b>Variant</b>   |              |                 |              |
| ◆ 6/3 l, UWL class 2   | 390 x 170 mm | 14.900 kilogram | 0935100005   |
| ◆ 4,5/3 l, UWL class 1   | 390 x 170 mm | 14.900 kilogram | 0935100085   |
| <b>Infobox</b>   |              |                 |              |
| * Complies with the following standards: ASME A112.19.2/CSA B45.1 and ASME A112.19.14  |              |                 |              |
| Sanitary ceramics with the special WonderGliss surface finish will remain clean and attractive-looking for a long time to come.<br>When ordering WonderGliss please add a "1" as eleventh digit to the model number.   |              |                 |              |
| <b>Accessory for ceramics</b>  |              |                 |              |
| Conversion set for back supply   |              | 0.200 kilogram  | 007508       |
| <b>Accessory</b>   |              |                 |              |
| Conversion set for back supply   |              | 0.500 kilogram  | 007504       |
| <b>Suitable products</b>   |              |                 |              |
| Toilet close-coupled (without cistern), washdown model, Outlet for Vario connector set, for horizontal and vertical outlet, length adjustable from 70 - 170 mm, and vario connecting bend, vertical outlet from 160 - 220 mm, fixings included, UWL class 1, 370 x 630 mm                | 370 x 630 mm |                 | 215509       |
| Toilet close-coupled (without cistern), washdown model, Outlet for Vario connector set, for horizontal and vertical outlet, length adjustable from 70 - 190 mm, and vario connecting bend, vertical outlet from 170 - 220 mm, fixings included, cUPC® listed*, UWL class 1, 370 x 700 mm | 370 x 700 mm |                 | 215609       |

|   |                     |               |
|---|---------------------|---------------|
| <p>Toilet close-coupled for SensoWash® (without cistern), only in combination with SensoWash, washdown model, Outlet for Vario connector set, for horizontal and vertical outlet, length adjustable from 70 - 190 mm, and vario connecting bend, vertical outlet from 170 - 220 mm, connecting elements for SensoWash with concealed connections included, fixings included, cUPC® listed*, UWL class 1, 370 x 700 mm</p> | <p>370 x 700 mm</p> | <p>215659</p> |
| <p>Toilet close-coupled washdown model, (without cistern), fixings included, horizontal outlet, UWL class 1, 370 x 630 mm</p>   | <p>370 x 630 mm</p> | <p>216209</p> |

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.*