

Location:




SYMMONS® Museo™

Shower System S-5301 Specification Submittal



Feature Highlights

- Symmons Shower System with lever handles
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Secondary integral volume control handle
- Showerhead, single mode #532SH
- Showerhead arm and flange
- Standard flow rate is 2.5 gpm (9.5 L/min)
Optional lower flow rate restrictor available 
- Polished chrome finish

Model Numbers

- S-5301
Shower System with Symmons Temptrol® pressure-balancing mixing valve p/n S-4001-BODY
- S-5301-TRM
Trim only, mixing valve ordered separately
- S-4001-BODY
Symmons Temptrol® mixing valve without trim
- S-4001-X-BODY
Symmons Temptrol® mixing valve without trim.
Valve includes integral service stops to allow water shut-off for service


Finish Options / Modifications

Append appropriate -suffix to model number

- STN Satin nickel
- BLK Polished graphite
 - Polished chrome (standard finish)



Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05



Options / Modifications

Append appropriate -suffix to model number

- IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
- X Symmons Temptrol® mixing valve, includes integral service stops to allow water shut-off for service, p/n S-4001-X-BODY. (Option only applies when ordering model S-5301)
- REV Reverse coring in valve for back to back installations; hot on right, cold on left, (available with -X integral stops only)
- L/HD Showerhead not included. (Includes showerhead arm and flange only)
-  -2.0 2.0 (7.6 L/min) flow rate restrictor
-  -1.5 1.5 (5.7 L/min) flow rate restrictor

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

Dimensions Museo Shower System, S-5301

