TOTO_®

MW6043046CUFG(A)

UltraMax[®] II 1G[®] / WASHLET[®] + S500e One-Piece Toilet - 1.0 GPF

FEATURES

- Concealed supply connection for seamless installation
- Ultra high-efficiency TORNADO FLUSH® (1.0GPF/3.8LPF)
- CEFIONTECT® glaze prevents debris from sticking to ceramic surfaces for easy cleaning
- Universal Height
- Decorative one-piece design with elongated bowl
- Chrome trip lever
- 12" Rough-in, supply line sold separately
- See Spec sheet SW3046AT40 for WASHLET features

MODELS & COMPONENTS

MW6043046CUFGA#01

With CEFIONTECT ceramic glaze, WASHLET+ S500e and Auto Flush

- CST604CUFGAT40

Elongated bowl with CEFIONTECT

- SW3046AT40

WASHLET+ S500e

- THU766

Auto Flush Kit

MW6043046CUFG#01

Same as MW6043046CUFGA without Auto Flush

- CST604CUFGAT40

Elongated bowl with CEFIONTECT

- SW3046AT40

WASHLET+ S500e

COLORS/FINISHES

Standard #01 Cotton

PRODUCT SPECIFICATION

The one-piece ultra high-efficiency TORNADO FLUSH toilet shall be 1.0GPF/3.8LPF. Universal Height Toilet with CEFIONTECT glaze finish. Toilet shall have high-profile tank, elongated front bowl and chrome trip lever. Toilet shall be **TOTO Model MW6043046CUFG___#01**.

See TOTO Specification sheet **SW3046AT40** for details on required WASHLET.



CEFIONTECT

WASHLET



CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA WaterSense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements









UltraMax® II 1G® / WASHLET®+ S500e One-Piece Toilet - 1.0 GPF

SPECIFICATIONS

Water Use
Flush System
Min. Water Pressure
Water Surface
Trap Diameter
1.0 GPF/3.8LPF
TORNADO FLUSH®
8 psi (static)
6-3/4" x 8-5/8"
2-1/8"

Trap Diameter 2-1/8"Rough-in 12"Trap Seal 2-1/8"

Warranty
One Year Limited Warranty

Material Vitreous china

 Shipping Weight CST604CUFGAT40 99lbs. SW3046AT40 15.6lbs.

Shipping Dimensions CST604CUFGAT40

32"L x 20"W x

17-3/4"H¹ x 28-3/4"H²

SW3046AT40


23-3/4"L X 17"W X 9-1/2"H

See Spec sheet SW3046AT40 for WASHLET details

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



Install this product according to the installation guide.

Will comply with ADA when installed per Section 604 Water Closetsand Toilet Compartments of the ADA 2010 Accessible Design Standard with seat height between 17" to 19", trip lever on approach side and flush actuation force of less than 5lbs.

Will comply with CSA B651 when installed per Clause 6.2.6 Toilets of the CSA 2012 Accessible Design Standard with seat height between 17" to 19", trip lever on approach side and flush actuation force of less than 5lbs.

